



Vitrone

rigid P.V.C. sheet

Worple Road 1

4. VITRONE EXTRUDED SHEET

- A. Vitraplus clear sheet for rooflights, domelights and space glazing. Of good weatherability and satisfying the fire requirements of BSS 476 part 7 Vitraplus is also protected both sides with strippable polythene film

Thickness range: 1.00 to 12.00 mm

Sheet size: 2440 x 1220 mm

3000 x 1220 mm

6000 x 1220 mm

3000 x 1500 mm

6000 x 1500 mm

other sizes by arrangement subject to minimum 50 sheet lots.

- B. Vitrone E industrial grey.

2 colours are available, dark grey RI153 and light grey RI117.

Vitrone E is suitable for all types of fabrication of process plant. It is also NON-TOXIC so can also be used for the fabrication of food handling equipment.

Size range is as for Vitraplus.

- C. Vitrone E colours.

Also in the same range of sizes as Vitraplus, Vitrone E can be supplied to colour match for minimum 5000 kg lots.

5. VITRONE PRESSED CLEAR WIRE LAMINATE

To complement Vitraplus, Vitrone clear wire laminate is available to satisfy the most stringent of fire regulations.

Satisfying BSS 476 part 3, it allows designers complete freedom in their choice of glazing materials.

FO

E. U.P.

P.E. Lam
patisserie
chill cabi
atmosph

Standard
300 micr
550 micr
650 micr
But othe

P.V.D.C.

of phar
some v
produc

PF

V:

1

2

3